HANSEN

Easy Fit Compression Fittings



Fully Compatible

Hansen Easy Fit Compression Fittings are fully compatible with all other Hansen fitting ranges.



Standards & Approvals



Hansen Easy Fit Compression Fittings in sizes 16mm to 110mm have achieved the esteemed WaterMark Certification for use in plumbing & drainage installations. Certification No:WMKA21978















Easy to Install




1. Cut the pipe with pipe cutters, knife or saw. Ensure a square cut of pipe ends. Clean burrs from pipe ends. Keep the pipe end clean and as free of scratches and imperfections as possible.



2. Undo the nut to the last thread, do not remove nut from the body.



3. Insert the pipe into the fitting through the Nut, White Grip Ring & Thrust Ring until it meets resistance at the O-Ring. Give the pipe a firm push past the O-Ring all the way until it hits the final stop point.



4. Firmly hand tighten the nut. Use a pair of poly grips for a further half turn past hand tight for final tightening on 40mm fittings and greater.

The hydraulic seal is created when the pipe passes the O-ring. Tightening the nut is to achieve pull out resistance of the pipe.

HANSEN PRODUCTS (NZ) LIMITED

PO Box 809 • Whangarei • New Zealand P: +64 9 430 4140 F: +64 9 430 4141

E: info@hansenproducts.com

W: www.hansenproducts.com

Available From:



Best Installed Value

In the late 1970's Bert Hansen developed a range of easy to use "cold fit pipe fittings" that revolutionised the way Kiwi farmers joined pipe.

Adding to the Easy Fit range of pipe fittings, Hansen introduces the new Easy Fit Compression Fittings designed specifically for joining Medium Density polyethylene pipe. Building on 50 years experience in the manufacturing of pipe fittings and valves, the sleek, compact design uses only the very best materials to withstand the harshest weather conditions.

Hansen Products knows the importance that pipe fittings play in the performance and control of fluid delivery, flow and pressure within a pipe system. This has seen Hansen Products build a reputation for providing high performance, easy to use, innovative, simple products that provide our customers with "Best Installed Value".

All Hansen products carry our Lifetime Warranty*

*For more information on our warranty please visit www.hansenproducts.com/legal.htm

High Quality Compression Fittings

Manufactured in NZ using Best Quality Materials to withstand the harshest weather conditions

Potable (Drinking) water approved

> Dependable High **Quality Threaded** components



High Pressure Rated

Sleek, Compact Design for easy installation

onto pipe

THREAD CONVERSIONS	
	2" - 50mm
3/4" - 20mm	2 ¹ / ₂ " - 63mm
1" - 25mm	3" - 75mm
1 ¹ / ₄ " - 32mm	4" - 100mm

1¹/₂" - 40mm

Compression Coupling Fittings

Coupling - HMDC



32mm 75mm 16mm 40mm 50mm 110mm 25mm

Reducing Coupling - HMDRC



20mm x 16mm 32mm x 25mm 25mm x 16mm 40mm x 25mm 40mm x 32mm 25mm x 20mm

50mm x 32mm 50mm x 40mm 63mm x 32mm 63mm x 40mm 63mm x 50mm 75mm x 63mm 90mm x 63mm

90mm x 75mm 110mm x 75mm 110mm x 90mm

Repair Slip Coupling -**HMDRSC**



20mm 50mm 25mm 32mm 63mm

63mm x 2"

63mm x 2 1/2"

Male Coupling - HMDMC

32mm x 1"



40mm x 1" 16mm x 1/2" 16mm x 3/4" 40mm x 2" 20mm x 1/2" 20mm x 3/4" 50mm x 1 1/2" 25mm x 3/4" 50mm x 2" 63mm x 1 1/4" 25mm x 1"

32mm x 1/2" 63mm x 1 1/2" 32mm x 3/4 63mm x 2" 63mm x 2 1/2" 32mm x 1 1/4" 75mm x 2 32mm x 1 1/2" 75mm x 2 1/2" 75mm x 3' 40mm x 1 1/4" 90mm x 2' 40mm x 1 1/2" 90mm x 2 1/2" 90mm x 3" 50mm x 1 1/4" 90mm x 4"

110mm x 2" 110mm x 3" 110mm x 4"

Female Coupling - HMDFC



32mm x 3/4" 75mm x 2" 75mm x 2 1/2" 32mm x 1" 32mm x 1 1/4' 75mm x 3" Size mm: 40mm x 1' 90mm x 2" 16mm x 1/2" 40mm x 1 1/4" 90mm x 2 1/2" 16mm x 3/4" 40mm x 1 1/2" 90mm x 3" 50mm x 1 1/4" 20mm x 1/2" 90mm x 4" 110mm x 2" 20mm x 3/4" 50mm x 1 1/2' 25mm x 1/2" 50mm x 2" 110mm x 3" 25mm x 3/4" 110mm x 4"

25mm x 1"

Compression Elbow Fittings

Elbow - HMDE



40mm 16mm 50mm 110mm 25mm 63mm

Male Elbow - HMDME 32mm x 1"



50mm x 1 1/2" 50mm x 2" 63mm x 1 1/2" Size mm: 16mm x 1/2" 63mm x 2" 63mm x 2 1/2" 16mm x 3/4" 20mm x 1/2" 75mm x 2 1/2" 20mm x 3/4" 75mm x 3" 25mm x 3/4" 90mm x 3" 25mm x 1" 90mm x 4" 32mm x 3/4" 110mm x 4"

32mm x 1 1/4"

40mm x 1 1/4"

40mm x 1 1/2"

40mm x 1"

Female Elbow - HMDFE

32mm x 3/4"



50mm x 1 1/2" Size mm: 50mm x 2" 63mm x 1 1/2" 16mm x 1/2" 20mm x 1/2" 63mm x 2" 75mm x 2 1/2" 20mm x 3/4" 25mm x 1/2' 75mm x 3" 25mm x 3/4" 90mm x 3" 25mm x 1" 90mm x 4"

110mm x 4"

O-Ring - HMDORING

40mm



16mm x 1/2" 25mm x 3/4 16mm x 3/4" 25mm x 1 20mm x 1/2" 32mm x 3/4" 20mm x 3/4" 32mm x 1"

20mm x 20mm x 16mm

25mm x 25mm x 20mm

32mm x 32mm x 25mm

40mm x 40mm x 32mm

32mm x 1 1/4 40mm x 1" 40mm x 1 1/4" 40mm x 1 1/2" 50mm x 1 1/2 50mm x 2" 63mm x 1 1/2" 63mm x 2" 75mm x 2 1/2" 75mm x 3' 90mm x 3" 110mm x 4"

50mm x 50mm x 32mm

50mm x 50mm x 40mm

63mm x 63mm x 50mm

75mm x 75mm x 63mm

90mm x 90mm x 75mm

110mm x 110mm x 63mm

110mm x 110mm x 90mm

Female Threaded Tee - HMDFT

Male Threaded Tee - HMDMT

Compression Tee Fittings

75mm

Tee - HMDT

16mm 25mm 40mm 20mm 32mm 50mm

Reducing Tee - HMDRT



Size mm: 25mm x 1 32mm x 1/2 16mm x 1/2" 32mm x 3/4" 16mm x 3/4" 20mm x 1/2" 32mm x 1" 32mm x 1 1/4" 20mm x 3/4" 25mm x 1/2" 40mm x 1"

50mm x 1 1/4" 50mm x 1 1/2" 50mm x 2" 63mm x 1 1/2" 63mm x 2" 63mm x 2 1/2 75mm x 2 75mm x 2 1/2" 75mm x 3" 90mm x 2 1/2" 90mm x 3" 110mm x 4"

Compression Cap Fitting

40mm x 1 1/4"

End Cap - HMDEC



25mm x 3/4"

Size mm: 16mm 20mm

32mm 63mm 110mm 40mm 75mm 50mm

Compression Spare Parts

Nut - HMDN

32mm

Thrust Ring - HMDTR



Size mm: 50mm 63mm 20mm 75mm 25mm 90mm 110mm 32mm

50mm Size mm: 63mm 20mm 75mm 25mm 90mm

Size mm: 50mm 16mm 63mm 20mm 75mm 25mm 90mm

Grip Ring - HMDGR

40mm

Size mm: 50mm 63mm 20mm 75mm 25mm 90mm 110mm

Hansen Easy Fit Compression Fittings are designed for Medium Density Polyethylene Pipe. Fitting sizes 16mm to 63mm are pressure rated to 16bar and sizes 75mm to 110mm to 12.5bar at 20° Celsius.