PRO-HC

Number of Stations: 6, 12, 24

Type: Fixed

FEATURES

- · Indoor and outdoor models
- Full-functioning controller with touchscreen
- Wi-Fi enabled for simple and fast connection to the internet
- 6, 12 and 24 fixed station controllers
- Dedicated master valve/pump start
- · Large terminal strips and wiring compartment
- · Built-in milliamp sensor across the full range of controllers
- Warranty period: 2 years
- ► Touchscreen Interface
- ► Predictive Water[™] Adjustments
- ► Flow Meter Detection and Alerts
- Wiring Detection and Alerts
- ► Advanced Sensor Ports

ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV: (24 VAC): 0.28 A
- Sensor inputs: 2
- Operating temperature: -18° C to 60° C

APPROVALS

• CE, UL, cUL, C-tick, FCC

HC - OPTIONS		
Models	Description	
HC-075-FLOW-B	Flow meter with 3/4" (20 mm) BSP thread	
HC-100-FLOW-B	Flow meter with 1" (25 mm) BSP thread	





Plastic Indoor

Height: 21 cm Width: 24 cm Depth: 8.8 cm

Plastic Outdoor

Height: 22.8 cm Width: 25 cm Depth: 10 cm



HC Flow Meter - 3/4" BSP thread

Height: 13 cm Length: 8 cm Depth: 8 cm

HC Flow Meter - 1" (25 mm) BSP thread

Height: 16 cm Length: 8 cm Depth: 8 cm



Compatible with Hydrawise software

PRO-HC - SPECIFICATION BUILDER: ORDER1 + 2 + 3 + 4				
1 Model	2 Transformer	3 Indoor/Outdoor	4 Options	
PHC-6 = 6-Station controller with Wi-Fi connection	00 = 120 VAC	(blank) = Outdoor model	(blank) = No option	
PHC-12 = 12-Station controller with Wi-Fi connection	01 = 230 VAC	(internal transformer)	E = 230 VAC with European connections	
PHC-24 = 24-Station controller with Wi-Fi connection		i = Indoor model (plug-in transformer)	A = 230 VAC with Australian connections (outdoor model has internal transformer with cord)	

Examples:

PHC-2400 = 24 station 120 VAC outdoor plastic controller

PHC-1201i-E = 12 station 230 VAC indoor plastic controller, with European connections