

RESIDENTIAL & COMMERCIAL IRRIGATION Built on Innovation®



- **Slim:** With a sleek, but durable body, the PS Ultra works well in tight spaces
- **O2 Compatible:** Works with all nozzles for easy retrofitting
- **Versatile:** PS Ultra is available in an array of sizes and pre-inserted nozzle options

PS ULTRA SLIM-LINE SPRAY SPRINKLER

PS Ultra Is the Slim Spray with All the Features For Any Installation

This compact slim-line spray sprinkler comes in 5 cm, 10 cm, and 15 cm models. Its innovative body incorporates a reliable two-piece ratchet, durable cap, male-threaded riser, and large filter screen, providing double filtration on 10 cm and 15 cm models. Additionally, the 5 cm and 10 cm models are retro-compatible with existing PS Spray bodies, which allow for a quick and easy upgrade. Standard PS Ultra models include a pre-installed Precision Distribution Control™ Adjustable Nozzle. A Flush Plug version is available without a nozzle or filter screen. With so many compatible nozzles to choose from, finding the most efficient solution for any application is simple and easy.

PS ULTRA FEATURES & SPECIFICATIONS

Features

- · Application: Residential
- Models: 5 cm, 10 cm, 15 cm
- Nozzle choices: 2.4 m, 3.0 m, 3.7 m, 4.6 m, 5.2 m, 1.5 x 9.0 m side strip (side strip pattern available on 5 and 10 cm models only)
- Optional preinstalled Precision Distribution Control™ Adjustable Nozzle
- Enhanced cap for more durability, easier handling, and extended riser seal life
- 5 cm and 10 cm models can retro-fit into older style PS sprays
- Two-piece ratchet
- Male threaded riser to accept all female nozzles
- Available with flush plug (large filter screen not included)
- Optional extra large filter screen
- Warranty period: 2 years

Specifications

- Recommended pressure range: 1.4 to 4.8 bar; 140 to 480 kPa
- Flow Rate: 0.72 to 21.75 l/min; 0.04 to 1.30 m^3/hr
- Radius: 2.2 m to 5.8 m
- Precipitation Rates: 35 to 42 mm/hr approx.

PS ULTRA - SPECIFICATION BUILDER: ORDER1 + 2 + 3 (OPTIONAL)Model Nozzles Optional PSU-02 = NFO = (blank) = Flush plug, no large filter screen Nozzle 5 cm Pon-un filter only **8A** = 2.4 m adjustable nozzle PSU-04 = (Available for **10A** = 3.0 m adjustable nozzle 10 cm Pop-up 10 cm model **12A** = 3.7 m adjustable nozzle PSU-06 = only) **15A** = 4.6 m adjustable nozzle 15 cm Pop-up **17A** = 5.2 m adjustable nozzle

5SS = $1.5 \,\text{m} \times 9.0 \,\text{m}$ side strip

(not available for PSU-06)

Examples:

PSU-04 - 15A = 10 cm pop-up, with a 4.6 m adjustable nozzle **PSU-02 - 5SS** = 5 cm pop-up, with a 1.5 m x 9.0 m side strip **PSU-06 - 10A** = 15 cm pop-up, with a 3.0 m adjustable nozzle **PSU-04 - 12A - NFO** = 10cm Pop-up, with a 3.7 m Adjustable nozzle, nozzle filter only

Models



[A] **PSU02**

Overall height: 12 cm Pop-up height: 5 cm Exposed diameter: 3 cm Inlet size: ½"

[B] **PSU04**

Overall height: 18 cm Pop-up height: 10 cm Exposed diameter: 3 cm Inlet size: ½"

[C] **PSU06**

Overall height: 24 cm Pop-up height: 15 cm Exposed diameter: 3 cm Inlet size: ½"

FLUSH PLUG

The PS Ultra comes equipped with a flush plug when ordered standard without a nozzle. The PS Ultra flush plug is composed of high quality materials and is directional, allowing the user to avoid uncontrolled flooding of the head area.



Website hunterindustries.com | Technical Service +1760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

