


# Gibault Couplings



No.	PRODUCT REF	Sizes in Imperial	Sizes in MM	L	L2	unit weight (kgs)	size ranges(mm)	pattern
1	couplings	1.5"	40	95	200	3.00	48-58	y
2	couplings	2"	50	100	200	3.55	59-72	y
3	couplings	2 1/2"	65	100	200	4.50	72-85	y
4	couplings	3"	80	100	200	4.96	88-103	y
5	couplings	4"	100	100	200	6.71	108-128	y
6	couplings	5"	125	100	200	7.48	132-154	y
7	couplings	6"	150	100	200	8.92	159-182	y
8	couplings	7"	175	100	200	9.70	192-209	y
9	couplings	8"	200	100	200	10.00	218-235	y
10	couplings	9"	225/250	100	200		250-267	
11	couplings	10"	250	100	200	15.40	271-289	y
12	couplings	12"	300	150	200	16.94	322-340	y
13	couplings	12"	300	150	200	16.94	315-332	y
14	couplings	14"	350	150	260	24.00	374-391	y
15	couplings	16"	400	150	260	26.90	417-437	y
16	couplings	18"	450	150	260	31.80	480-500	y
17	couplings	20"	500	150	260	40.00	526-546	y
18	couplings	24"	600	150	260	44.10	630-650	y

**Note:**

- 1 All the couplings are assembled by "D" bolts. 2 1/2", 3", 4", 5", 6", 7", 8" are with four bolts holes. 10", 12" have six bolt holes, 14", 16" has eight holes, 18", 20", 24" are with ten bolt holes.
- 2 epoxy coated in blue, black, red or at customers' request.
- 3 bolts in carbon steel grade 8.8 with dacromet coating.
- 4 rubber rings in E.P.D.M.
- 5 package: in wooden cases with bubble plastic bags for each item.