



UNIBIOLINE 16010 AS

HEAVY WALL, PRESSURE COMPENSATING & ANTI SIPHON 16mm LILAC DRIPPERLINE

APPLICATIONS

- Domestic & commercial onsite water re-use applications

FEATURES AND BENEFITS

- Patented TurboNet™ Dripper Technology - wide flow passage
- Pressure Compensated (PC) - self regulates to ensure uniform drip discharge
- Anti-Siphon (AS) dripper - prevents suck back
- Centrally mounted dripper with large inlet filter
- Mechanical root barrier
- Approved by the Smart WaterMark™

SPECIFICATIONS

- Pressure compensated (PC) & Anti-Siphon (AS) dripperline
- Operating Pressure: 100 kPa - 350 kPa
- Recommended filtration: 120 mesh (130 micron)
- Tubing colour: co-extruded lilac tube (indicates non-potable water)
- UV resistant Low Density Polyethylene (LDPE)
- Additional flow rates, spacings and pipe sizes are available on request. Minimum quantities apply.

DRIPPER TECHNICAL DATA

INSIDE DIAMETER (MM)	OUTSIDE DIAMETER (MM)	DRIPPER FLOW RATE (L/H)	DRIPPER SPACING (M)	PRESSURE RANGE (kPa)	COIL LENGTH (M)
14.2	16.2	1.6, 2.3 & 3.5	0.5, 0.6 & 1.0	100 - 350	100

TECHNICAL DATA

Maximum run length (m) on flat ground

NOMINAL FLOW RATE (L/H)	100 kPa	150 kPa	200 kPa	250 kPa	300 kPa
1.6 l/h @ 0.5m	N/A	122m	156m	179m	198m
2.3 l/h @ 0.6m	N/A	112m	143m	165m	181m
3.5 l/h @ 1.0m	N/A	129m	165m	190m	210m

SUITABLE FITTINGS

SAP	DESCRIPTION	SAP	DESCRIPTION
32500-013750	16mm Start Take-off to suit LDPE	32500-012500	16mm Elbow
00005-011500	16mm Elbow Take-off to suit LDPE	32500-011300	16mm Tee
45000-001650	16mm Take-off to suit LDPE	32500-010700	16mm Joiner
32500-013700	Straight Take-off with Grommet to suit PVC	76400-011750	16mm Herbie Clip Ratchet Clamp
00025-002400	Hold Down Stake (Asta)	00005-002200	16mm Ratchet Clamp
00005-008620	16mm Purple Shut-off Valve	76860-006400	150mm Round Box Valve - Green

For more information, please contact Netafim at www.netafim.co.nz



WWW.NETAFIM.CO.NZ
EMAIL: AUCKLAND@NETAFIM.CO.NZ

